



Spool Specifications

Drums




| PACKAGE TYPE | FLANGE | | BARREL | | TRAVERSE LENGTH (T-IN.) | OVERALL LENGTH (L-IN) | ARBOR HOLE DIAM. (A-IN) | TARE WEIGHT (POUNDS) | | NOM. NET WEIGHT (POUNDS) | |
|--------------|-------------|----------------|-------------|----------------|-------------------------|-----------------------|-------------------------|----------------------|-------------|--------------------------|----------|
| | TOP (d-IN.) | BOTTOM (D-IN.) | TOP (b-IN.) | BOTTOM (B-IN.) | | | | PLASTIC | FIBER/METAL | COPPER | ALUMINUM |
| | Drum | 20 | 20 | 13 | | | | | | | |
| ½ Drum | 20 | 20 | 13 | 13 | — | 15 | — | 12 | 250 | 90 | |
| Pail | 11 | 11 | 7 | 7 | — | 12 | — | 3 | 85 | 30 | |

Tapered Spools




| PACKAGE TYPE | FLANGE | | BARREL | | TRAVERSE LENGTH (T-IN.) | OVERALL LENGTH (L-IN) | ARBOR HOLE DIAM. (A-IN) | TARE WEIGHT (POUNDS) | | NOM. NET WEIGHT (POUNDS) | |
|--------------|-------------|----------------|-------------|----------------|-------------------------|-----------------------|-------------------------|----------------------|-------------|--------------------------|----------|
| | TOP (d-IN.) | BOTTOM (D-IN.) | TOP (b-IN.) | BOTTOM (B-IN.) | | | | PLASTIC | FIBER/METAL | COPPER | ALUMINUM |
| | TP1000 | 18¾ | 20½ | 9 | | | | | | | |
| TP500 | 15 | 16 | 8 | 9 | 24 | 26 | 1½ | 12 | — | 500 | 180 |
| TP250 | 15 | 16 | 8 | 9 | 12 | 14 | 1½ | 10 | 15.0 | 250 | 90 |
| TP100 | 10 | 11 | 6 | 7 | 12 | 13 | 1½ | 3.05 | 8.0 | 85 | 30 |
| TP50 | 8½ | 9¼ | 5½ | 6½ | 9 | 10 | 1½ | 1.6 | — | 45 | — |

Straight Spools



| PACKAGE TYPE | FLANGE | | BARREL | | TRAVERSE LENGTH (T-IN.) | OVERALL LENGTH (L-IN) | ARBOR HOLE DIAM. (A-IN) | TARE WEIGHT (POUNDS) | | NOM. NET WEIGHT (POUNDS) | |
|--------------|-------------|----------------|-------------|----------------|-------------------------|-----------------------|-------------------------|----------------------|-------------|--------------------------|----------|
| | TOP (d-IN.) | BOTTOM (D-IN.) | TOP (b-IN.) | BOTTOM (B-IN.) | | | | PLASTIC | FIBER/METAL | COPPER | ALUMINUM |
| | 30" | 30 | 30 | 14 | | | | | | | |
| 24" | 24 | 24 | 14 | 14 | 6 | 8⅞ | 1½ | 20 | — | 250 | 80 |
| 12" x 7" | 12 | 12 | 6½ | 6½ | 7 | 8 | 1½ | 2.8 | — | 85 | 26 |
| 12" x 4" WR | 11¾ | 11¾ | 8¼ | 8¼ | 3⅝ | 4 | 2 | 1.8 | — | 30 | 10 |
| 8" x 6" | 8 | 8 | 4½ | 4½ | 5⅝ | 7¼ | 3 | 1.5 | — | 30 | 10 |
| 6" x 6" | 6 | 6 | 3¾ | 3¾ | 6 | 7 | ⅝ | .95 | — | 12 | 5 |
| 6" DIN * | 6¼ | 6¼ | 4 | 4 | 5 | 6¼ | ⅞ | 1.02 | — | 10 | 3 |
| 6" X 3½" * | 6 | 6 | 3½ | 3½ | 3½ | 4⅝ | ⅝ | .66 | — | 8 | 3 |
| 6" X 3½" | 6 | 6 | 3½ | 3½ | 3½ | 4 | ⅝ | .43 | — | 8 | 3 |
| 6" RB | 6 | 6 | 4 | 4 | 3 | 4 | ⅝ | .64 | — | 8 | 3 |
| 4⅞" DIN * | 4⅞ | 4⅞ | 3⅞ | 3⅞ | 4 | 4⅞ | ⅝ | .55 | — | 6 | 2 |
| 5" RB | 5 | 5 | 4 | 4 | 3 | 4 | ⅝ | .55 | — | 4 | 1.5 |
| 4⅞ | 4⅞ | 4⅞ | 3 | 3 | 3½ | 4 | ⅝ | .39 | — | 5 | 2 |
| 3" | 3 | 3 | 1¾ | 1¾ | 3½ | 4 | ⅝ | .17 | — | 2 | .5 |
| 3" DIN * | 3⅞ | 3⅞ | 2 | 2 | 2½ | 3⅝ | ⅝ | .15 | — | 1 | .30 |
| 2½" | 2½ | 2½ | 1¾ | 1¾ | 3 | 3⅞ | ⅝ | .15 | — | .5 | .15 |
| 2¼" | 2¼ | 2¼ | 1¾ | 1¾ | 1 | 1⅝ | ⅝ | .09 | — | .20 | .07 |

Taper Flange Spools



| PACKAGE TYPE | FLANGE | | BARREL | | TRAVERSE LENGTH (T-IN.) | OVERALL LENGTH (L-IN) | ARBOR HOLE DIAM. (A-IN) | TARE WEIGHT (POUNDS) | | NOM. NET WEIGHT (POUNDS) | |
|--------------|-------------|----------------|-------------|----------------|-------------------------|-----------------------|-------------------------|----------------------|-------------|--------------------------|----------|
| | TOP (d-IN.) | BOTTOM (D-IN.) | TOP (b-IN.) | BOTTOM (B-IN.) | | | | PLASTIC | FIBER/METAL | COPPER | ALUMINUM |
| | 10" TF | 10 | 11 | 6 | | | | | | | |
| 8" TF | 8 | 8 | 4 | 4 | 3⅝ - 7⅝ | 8 | ⅞ | .98 | — | 22 | — |
| 6" TF | 6 | 6 | 3⅞ | 3⅞ | 3 - 5¼ | 6¼ | ⅝ - ⅞ | .69 | — | 8 | 3 |
| 5" TF | 4⅞ | 4⅞ | 2½ | 2½ | 2¼ - 4 | 4⅞ | ⅝ | .35 | — | 5 | 1.75 |
| 4" TF | 4 | 4 | 2 | 2 | 1⅞ - 3¼ | 4 | ⅝ | .15 | — | 3 | 1 |
| 3" TF | 3 | 3 | 2¼ | 2 | 2¼ - 3¼ | 3⅞ | ⅝ | .19 | — | 1.5 | .5 |
| 2½" TF | 2½ | 2½ | 1¾ | 1¾ | 2⅞ - 3¼ | 3⅞ | ⅝ | .16 | — | .66 | .15 |

*Thick flange