



# Spool Specifications

## Tapered Spools



PACKAGE TYPE	FLANGE		BARREL		TRAVERSE LENGTH (T-IN.)	OVERALL LENGTH (L-IN.)	ARBOR HOLE DIAM. (A-IN.)	TARE WEIGHT (POUNDS)	NOM. NET WEIGHT (POUNDS)	
	TOP (d-IN.)	BOTTOM (B-IN.)	TOP (b-IN.)	BOTTOM (B-IN.)					PLASTIC	COPPER
TP1000	18 $\frac{3}{4}$	20 $\frac{1}{2}$	9	10 $\frac{1}{2}$	18 $\frac{5}{16}$	36 $\frac{7}{8}$	1 $\frac{1}{2}$	30	1000	300
TP500	15	16	8	9	24	26	1 $\frac{1}{2}$	12	500	180
TP250	15	16	8	9	12	14	1 $\frac{1}{2}$	10	250	90
TP100	10	11	6	7	12	13	1 $\frac{1}{2}$	3.05	85	30
TP50	8 $\frac{1}{2}$	9 $\frac{1}{4}$	5 $\frac{1}{2}$	6 $\frac{1}{2}$	9	10	1 $\frac{1}{2}$	1.6	5	2


## Straight Spools



PACKAGE TYPE	FLANGE		BARREL		TRAVERSE LENGTH (T-IN.)	OVERALL LENGTH (L-IN.)	ARBOR HOLE DIAM. (A-IN.)	TARE WEIGHT (POUNDS)	NOM. NET WEIGHT (POUNDS)	
	TOP (B-IN.)	BOTTOM (B-IN.)	TOP (B-IN.)	BOTTOM (B-IN.)					PLASTIC	COPPER
24"	24	24	14	14	6	8 $\frac{7}{8}$	1 $\frac{1}{2}$	20	250	80
12" x 7"	12	12	6 $\frac{1}{2}$	6 $\frac{1}{2}$	7	8	1 $\frac{1}{2}$	2.8	85	26
12" x 4" WR	11 $\frac{1}{4}$	11 $\frac{1}{4}$	8 $\frac{1}{4}$	8 $\frac{1}{4}$	3 $\frac{5}{8}$	4	2	1.8	30	10
8" x 6"	8	8	4 $\frac{1}{2}$	4 $\frac{1}{2}$	5 $\frac{5}{8}$	7 $\frac{1}{4}$	3	1.5	30	10
6" x 6"	6	6	3 $\frac{3}{4}$	3 $\frac{3}{4}$	6	7	$\frac{5}{8}$	.95	12	5
6" DIN *	6 $\frac{1}{4}$	6 $\frac{1}{4}$	4	4	5	6 $\frac{1}{4}$	7 $\frac{1}{8}$	1.02	10	3
6" X 3 $\frac{1}{2}$ "*	6	6	3 $\frac{1}{2}$	3 $\frac{1}{2}$	3 $\frac{1}{2}$	4 $\frac{5}{16}$	$\frac{5}{8}$	.66	8	3
6" X 3 $\frac{1}{2}$ "	6	6	3 $\frac{1}{2}$	3 $\frac{1}{2}$	3 $\frac{1}{2}$	4	$\frac{5}{8}$	.43	8	3
6" RB	6	6	4	4	3	4	$\frac{5}{8}$	.64	8	3
4 $\frac{7}{8}$ " DIN*	4 $\frac{7}{8}$	4 $\frac{7}{8}$	3 $\frac{3}{16}$	3 $\frac{3}{16}$	4	4 $\frac{7}{8}$	$\frac{5}{8}$	.55	6	2
4 $\frac{7}{8}$	4 $\frac{7}{8}$	4 $\frac{7}{8}$	3	3	3 $\frac{1}{2}$	4	$\frac{5}{8}$	.39	5	2
3"	3	3	1 $\frac{3}{4}$	1 $\frac{3}{4}$	3 $\frac{1}{2}$	4	$\frac{5}{8}$	.17	2	.5
3" DIN *	3 $\frac{3}{8}$	3 $\frac{3}{8}$	2	2	2 $\frac{1}{2}$	3 $\frac{5}{32}$	$\frac{5}{8}$	.15	1	.30
2 $\frac{1}{2}$ "	2 $\frac{1}{2}$	2 $\frac{1}{2}$	1 $\frac{3}{4}$	1 $\frac{3}{4}$	3	3 $\frac{3}{8}$	$\frac{5}{8}$	.15	.5	.15
2 $\frac{1}{4}$ "	2 $\frac{1}{4}$	2 $\frac{1}{4}$	1 $\frac{3}{4}$	1 $\frac{3}{4}$	1	1 $\frac{5}{16}$	$\frac{5}{8}$	.09	.20	.07

\*Thick flange

## Taper Flange Spools



PACKAGE TYPE	FLANGE		BARREL		TRAVERSE LENGTH (T-IN.)	OVERALL LENGTH (L-IN.)	ARBOR HOLE DIAM. (A-IN.)	TARE WEIGHT (POUNDS)	NOM. NET WEIGHT (POUNDS)	
	TOP (B-IN.)	BOTTOM (B-IN.)	TOP (B-IN.)	BOTTOM (B-IN.)					PLASTIC	COPPER
10" TF	10	11	6	7	8 - 11 $\frac{1}{2}$	12 $\frac{1}{2}$	1 $\frac{1}{2}$	3.12	75	20
8" TF	8	8	4	4	3 $\frac{5}{8}$ - 7 $\frac{5}{8}$	8	7 $\frac{1}{8}$	.98	22	6
6" TF	6	6	3 $\frac{1}{8}$	3 $\frac{1}{8}$	3 - 5 $\frac{1}{4}$	6 $\frac{1}{4}$	$\frac{5}{8}$ - 7 $\frac{1}{8}$	.69	8	3
5" TF	4 $\frac{7}{8}$	4 $\frac{7}{8}$	2 $\frac{1}{2}$	2 $\frac{1}{2}$	2 $\frac{1}{4}$ - 4	4 $\frac{7}{8}$	$\frac{5}{8}$	.35	5	1.75
4" TF	4	4	2	2	1 $\frac{7}{8}$ - 3 $\frac{3}{4}$	4	$\frac{5}{8}$	.15	3	1
3" TF	3	3	2 $\frac{3}{4}$	2	2 $\frac{3}{4}$ - 3 $\frac{3}{4}$	3 $\frac{7}{8}$	$\frac{5}{8}$	.19	1.5	.5
2 $\frac{1}{2}$ " TF	2 $\frac{1}{2}$	2 $\frac{1}{2}$	1 $\frac{3}{4}$	1 $\frac{3}{4}$	2 $\frac{3}{8}$ - 3 $\frac{1}{4}$	3 $\frac{3}{8}$	$\frac{5}{8}$	.16	.66	.15